# **APPENDIX G**

GHG Emissions Worksheets & Methodology

# Greenhouse Gas Emissions Worksheets for the New Whatcom Redevelopment Project Supplemental Draft EIS

October 2008

# New Whatcom Redevelopment Project SDEIS - Preferred Alternative

### Section I: Buildings

Emissions Per Unit or Per Thousand Square Feet (MTCO2e)

		Square Feet (in				Lifespan
Type (Residential) or Principal Activity		thousands of				<b>Emissions</b>
(Commercial)	# Units	square feet)	Embodied	Energy	Transportation	(MTCO2e)
Single-Family Home	0		98	672	792	0
Multi-Family Unit in Large Building	1892		33	357	766	2186574
Multi-Family Unit in Small Building	0		54	681	766	0
Mobile Home	0		41	475	709	0
Education		670.0	39	646	361	700472
Food Sales		0.0	39	1,541	282	0
Food Service		65.0	39	1,994	561	168598
Health Care Inpatient		0.0	39	1,938	582	0
Health Care Outpatient		0.0	39	737	571	0
Lodging		0.0	39	777	117	0
Retail (Other Than Mall)		310.0	39	577	247	267454
Office		2,000.0	39	723	588	2698690
Public Assembly		0.0	39	733	150	0
Public Order and Safety		0.0	39	899	374	0
Religious Worship		0.0	39	339	129	0
Service		0.0	39	599	266	0
Warehouse and Storage		0.0	39	352	181	0
Other		685.0	39	1,278	257	1078310
Vacant		0.0	39	162	47	0

Section II: Pavement.....

Pavement	3,023.00		151150
----------	----------	--	--------

**Total Project Emissions:** 

7251248

# New Whatcom Redevelopment Project DEIS Alternative 4 - No Action Alternative

### Section I: Buildings

Emissions Per Unit or Per Thousand Square Feet (MTCO2e)

		Square Feet (in				Lifespan
Type (Residential) or Principal Activity		thousands of				<b>Emissions</b>
(Commercial)	# Units	square feet)	Embodied	Energy	Transportation	(MTCO2e)
Single-Family Home	0		98	672	792	0
Multi-Family Unit in Large Building	0		33	357	766	0
Multi-Family Unit in Small Building	0		54	681	766	0
Mobile Home	0		41	475	709	0
Education		0.0	39	646	361	0
Food Sales		0.0	39	1,541	282	0
Food Service		0.0	39	1,994	561	0
Health Care Inpatient		0.0	39	1,938	582	0
Health Care Outpatient		0.0	39	737	571	0
Lodging		0.0	39	777	117	0
Retail (Other Than Mall)		0.0	39	577	247	0
Office		0.0	39	723	588	0
Public Assembly		0.0	39	733	150	0
Public Order and Safety		0.0	39	899	374	0
Religious Worship		0.0	39	339	129	0
Service		0.0	39	599	266	0
Warehouse and Storage		190.0	39	352	181	108632
Other		2,000.0	39	1,278	257	3148351
Vacant		0.0	39	162	47	0

Section II: Pavement.....

**Total Project Emissions:** 

3510083

King County Department of Development and Environmental Services Greenhouse Gas Emissions Worksheet Methodology

# King County Department of Development and Environmental Services SEPA GHG Emissions Worksheet Version 1.7 12/26/07

### Introduction

The Washington State Environmental Policy Act (SEPA) requires environmental review of development proposals that may have a significant adverse impact on the environment. If a proposed development is subject to SEPA, the project proponent is required to complete the SEPA Checklist. The Checklist includes questions relating to the development's air emissions. The emissions that have traditionally been considered cover smoke, dust, and industrial and automobile emissions. With our understanding of the climate change impacts of GHG emissions, King County requires the applicant to also estimate these emissions.

### Emissions created by Development

GHG emissions associated with development come from multiple sources:

- The extraction, processing, transportation, construction and disposal of materials and landscape disturbance (Embodied Emissions)
- Energy demands created by the development after it is completed (Energy Emissions)
- Transportation demands created by the development after it is completed (Transportation Emissions)

### **GHG Emissions Worksheet**

King County has developed a GHG Emissions Worksheet that can assist applicants in answering the SEPA Checklist question relating to GHG emissions.

The SEPA GHG Emissions worksheet estimates all GHG emissions that will be created over the life span of a project. This includes emissions associated with obtaining construction materials, fuel used during construction, energy consumed during a buildings operation, and transportation by building occupants.

### Using the Worksheet

 Descriptions of the different residential and commercial building types can be found on the second tabbed worksheet ("Definition of Building Types"). If a development proposal consists of multiple projects, e.g. both single family and multi-family residential structures or a commercial development that consists of more than on type of commercial activity, the appropriate information should be estimated for each type of building or activity.

- 2. For paving, estimate the total amount of paving (in thousands of square feet) of the project.
- The Worksheet will calculate the amount of GHG emissions associated with the project and display the amount in the "Total Emissions" column on the worksheet. The applicant should use this information when completing the SEPA checklist.
- 4. The last three worksheets in the Excel file provide the background information that is used to calculate the total GHG emissions.
- 5. The methodology of creating the estimates is transparent; if there is reason to believe that a better estimate can be obtained by changing specific values, this can and should be done. Changes to the values should be documented with an explanation of why and the sources relied upon.
- 6. Print out the "Total Emissions" worksheet and attach it to the SEPA checklist. If the applicant has made changes to the calculations or the values, the documentation supporting those changes should also be attached to the SEPA checklist.

Definition of Building Types	
Type (Residential) or Principal Activi	
(Commercial)	Description
Single-Family Home	Unless otherwise specified, this includes both attached and detached building
Multi-Family Unit in Large Building	
Multi-Family Unit in Small Building	
Mobile Home	
Education	Buildings used for academic or technical classroom instruction, such as elementary, middle, or high schools, and classroom buildings on college or university campuses. Buildings on education campuses for which the main use is not classroom are included in the category relating to their use. For example, administration buildings are part of "Office," dormitories are "Lodging," and libraries are "Public Assembly."
Food Sales	
Food Service	
Health Care Inpatient	Buildings used as diagnostic and treatment facilities for inpatient care.
Health Care Outpatient	Buildings used as diagnostic and treatment facilities for outpatient care.  Doctor's or dentist's office are included here if they use any type of diagnostic medical equipment (if they do not, they are categorized as an office building).
Lodging	
Retail (Other Than Mall)	
Office	Buildings used for general office space, professional office, or administrative offices. Doctor's or dentist's office are included here if they do not use any type of diagnostic medical equipment (if they do, they are categorized as an outpatient health care building).
	Buildings in which people gather for social or recreational activities, whether in
Public Assembly	
Public Order and Safety	
Religious Worship	Buildings in which people gather for religious activities, (such as chapels, churches, mosques, synagogues, and temples).
	Buildings in which some type of service is provided, other than food service or
Service	
	Buildings used to store goods, manufactured products, merchandise, raw
Warehouse and Storage	
	Buildings that are industrial or agricultural with some retail space; buildings having several different commercial activities that, together, comprise 50 percent or more of the floorspace, but whose largest single activity is agricultural, industrial/ manufacturing, or residential; and all other
Other	miscellaneous buildings that do not fit into any other category.  Buildings in which more floorspace was vacant than was used for any single commercial activity at the time of interview. Therefore, a vacant building may
Vacant	have some occupied floorspace.

### Sources: .....

Residential

2001 Residential Energy Consumption Survey Square footage measurements and comparisons http://www.eia.doe.gov/emeu/recs/sqft-measure.html

Commercial

Commercial Buildings Energy Consumption Survey (CBECS),

Description of CBECS Building Types

http://www.eia.doe.gov/emeu/cbecs/pba99/bldgtypes.html

### **Embodied Emissions Worksheet**

	Life span related	Life span related embodied
# thousand	embodied GHG	GHG missions (MTCO2e/
sq feet/ unit	missions (MTCO2e/	thousand square feet) - See
or building	unit)	calculations in table below
2.53	98	39
0.85	33	39
1.39	54	39
1.06	41	39
25.6	991	39
5.6	217	39
5.6	217	39
241.4	9,346	39
10.4	403	39
35.8	1,386	39
9.7	376	39
14.8	573	39
14.2	550	39
15.5	600	39
10.1	391	39
6.5	252	39
16.9	654	39
21.9	848	39
14.1	546	39
	sq feet/ unit or building 2.53 0.85 1.39 1.06 25.6 5.6 241.4 10.4 35.8 9.7 14.2 15.5 10.1 6.5	# thousand sq feet/ unit or building a feet/ unit or building a feet unit or b

Section II: Pavement..

All Types of Pavement..

		Intermediate			Interior			
	Columns and Beams	Floors	Exterior Walls	Windows	Walls	Roofs		
Average GWP (lbs CO2e/sq ft): Vancouver,								
Low Rise Building	5.3	7.8	19.1	51.2	5.7	21.3		
							Total	Total Embodied
							Embodied	Emissions
Average Materials in a 2,272-square foot							Emissions	(MTCO2e/
single family home	0.0	2269.0	3206.0	285.0	6050.0	3103.0	(MTCO2e)	thousand sq feet)
MTCO2e	0.0	8.0	27.8	6.6	15.6	30.0	88.0	38.7

Sources
All data in black text King County, DNRP. Contact: Matt Kuharic, matt.kuharic@kingcounty.gov

Residential floorspace per unit 2001 Residential Energy Consumption Survey (National Average, 2001)

Square footage measurements and comparisons http://www.eia.doe.gov/emeu/recs/sqft-measure.html

Floorspace per building EIA, 2003 Commercial Buildings Energy Consumption Survey (National Average, 2003)

Table C3. Consumption and Gross Energy Intensity for Sum of Major Fuels for Non-Mall Buildings, 2003 http://www.eia.doe.gov/emeu/cbecs/cbecs2003/detailed\_tables\_2003/2003set9/2003excel/c3.xls

### Average GWP (lbs CO2e/sq ft): Vancouver,

Low Rise Building

Athena EcoCalculator

Athena Assembly Evaluation Tool v2.3- Vancouver Low Rise Building Assembly Average GWP (kg) per square meter

http://www.athenasmi.ca/tools/ecoCalculator/index.html Lbs per kg 2.20 Square feet per square meter 10.76

Average Materials in a 2,272-square foot

single family home

Buildings Energy Data Book: 7.3 Typical/Average Household

Materials Used in the Construction of a 2,272-Square-Foot Single-Family Home, 2000 http://buildingsdatabook.eren.doe.gov/?id=view\_book\_table&TableID=2036&t=xls See also: NAHB, 2004 Housing Facts, Figures and Trends, Feb. 2004, p. 7.

Appendix B, Quality of the Data. Pg. 5.

ftp://ftp.eia.doe.gov/pub/consumption/residential/rx93hcf.pdf

Pavement Emissions Factors
MTCO2e/thousand square feet of asphalt
or concrete pavement

50 (see below)

### Embodied GHG Emissions......Worksheet Background Information

### Ruilding

Embodied GHG emissions are emissions that are created through the extraction, processing, transportation, construction and disposal of building materials as well as emissions created through landscape disturbance (by both soil disturbance and changes in above ground biomass).

Estimating embodied GHG emissions is new field of analysis; the estimates are rapidly improving and becoming more inclusive of all elements of construction and development.

The estimate included in this worksheet is calculated using average values for the main construction materials that are used to create a typical family home. In 2004, the National Association of Home Builders calculated the average materials that are used in a typical 2,272 square foot single-family household. The quantity of materials used is then multiplied by the average GHG emissions associated with the life-cycle GHG emissions for each material.

This estimate is a rough and conservative estimate; the actual embodied emissions for a project are likely to be higher. For example, at this stage, due to a lack of comprehensive data, the estimate does not include important factors such as landscape disturbance or the emissions associated with the interior components of a building (such as furniture).

King County realizes that the calculations for embodied emissions in this worksheet are rough. For example, the emissions associated with building 1,000 square feet of a residential building will not be the same as 1,000 square feet of a commercial building. However, discussions with the construction community indicate that while there are significant differences between the different types of structures, this method of estimation is reasonable; it will be improved as more data become available.

Additionally, if more specific information about the project is known, King County recommends two online embodied emissions calculators that can be used to obtain a more tailored estimate for embodied emissions: <a href="https://www.athenasmi.ca/tools/ecoCalculator/">www.athenasmi.ca/tools/ecoCalculator/</a>.

### Pavement

Four recent life cycle assessments of the environmental impacts of roads form the basis for the per unit embodied emissions of pavement. Each study is constructed in slightly different ways; however, the aggregate results of the reports represent a reasonable estimate of the GHG emissions that are created from the manufacture of paving materials, construction related emissions, and maintenance of the pavement over its expected life cycle. For specifics, see the worksheet.

### Special Section: Estimating the Embodied Emissions for Pavement

Four recent life cycle assessments of the environmental impacts of roads form the basis for the per unit embodied emissions of pavement. Each study is constructed in slightly different ways; however, the aggregate results of the reports represent a reasonable estimate of the GHG emissions that are created from the manufacture of paving materials, construction related emissions, and maintenance of the pavement over its expected life cycle.

The results of the studies are presented in different units and measures; considerable effort was undertaken to be able to compare the results of the studies in a reasonable way. For more details about the below methodology, contact matt.kuharic@kingcounty.gov.

The four studies, Meil (2001), Park (2003), Stripple (2001) and Treolar (2001) produced total GHG emissions of 4-34 MTCO2e per thousand square feet of finished paving (for similar asphalt and concrete based pavements). This estimate does not including downstream maintenance and repair of the highway. The average (for all concrete and asphalt pavements in the studies, assuming each study gets one data point) is ~17 MTCO2e/thousand square feet.

Three of the studies attempted to thoroughly account for the emissions associated with long term maintenance (40 years) of the roads. Stripple (2001), Park et al. (2003) and Treolar (2001) report 17, 81, and 68 MTCO2e/thousand square feet, respectively, after accounting for maintenance of the roads.

Based on the above discussion, King County makes the conservative estimate that 50 MTCO2e/thousand square feet of pavement (over the development's life cycle) will be used as the embodied emission factor for pavement until better estimates can be obtained. This is roughly equivalent to 3,500 MTCO2e per lane mile of road (assuming the lane is 13 feet wide).

It is important to note that these studies estimate the embodied emissions for roads. Paving that does not need to stand up to the rigors of heavy use (such as parking lots or driveways) would likely use less materials and hence have lower embodied emissions.

### Sources 4 8 1

Meil, J. A Life Cycle Perspective on Concrete and Asphalt Roadways: Embodied Primary Energy and Global Warming Potential. 2006. Available:

http://www.cement.ca/cement.nsf/eee9ec7bbd630126852566c40052107b/6ec79dc8ae03a782852572b90061b9

Park, K, Hwang, Y., Seo, S., M.ASCE, and Seo, H., "Quantitative Assessment of Environmental Impacts on Life Cycle of Highways," Journal of Construction Engineering and Management, Vol 129, January/February 2003, pp 25-31, (DOI: 10.1061/(ASCE)0733-9364(2003)129:1(25)).

Stripple, H. Life Cycle Assessment of Road. A Pilot Study for Inventory Analysis. Second Revised Edition. IVL Swedish Environmental Research Institute Ltd. 2001. Available: http://www.ivl.se/rapporter/pdf/B1210E.pdf

Treloar, G., Love, P.E.D., and Crawford, R.H. Hybrid Life-Cycle Inventory for Road Construction and Use. Journal of Construction Engineering and Management. P. 43-49. January/February 2004.

**Energy Emissions Worksheet** 

	Energy			Floorspace	MTCE per				Lifespan Energy
	consumption per			per Building					
Type (Residential) or Principal Activity	building per year		· ·		square feet per	thousand square	Building Life		
(Commercial)		Buildings	building per year	square feet)	year	feet per year	Span	emissions per unit	thousand square feet
Single-Family Home	107.3	0.108	11.61	2.53	4.6	16.8	57.9	672	266
Multi-Family Unit in Large Building	41.0	0.108	4.44	0.85	5.2	19.2	80.5	357	422
Multi-Family Unit in Small Building	78.1	0.108	8.45	1.39	6.1	22.2	80.5	681	489
Mobile Home	75.9	0.108	8.21	1.06	7.7	28.4	57.9	475	448
Education	2,125.0	0.124	264.2	25.6	10.3	37.8	62.5	16,526	646
Food Sales	1,110.0	0.124	138.0	5.6	24.6	90.4	62.5	8,632	1,541
Food Service	1,436.0	0.124	178.5	5.6	31.9	116.9	62.5	11,168	1,994
Health Care Inpatient	60,152.0	0.124	7,479.1	241.4	31.0	113.6	62.5	467,794	1,938
Health Care Outpatient	985.0	0.124	122.5	10.4	11.8	43.2	62.5	7,660	737
Lodging	3,578.0	0.124	444.9	35.8	12.4	45.6	62.5	27,826	777
Retail (Other Than Mall)	720.0	0.124	89.5	9.7	9.2	33.8	62.5	5,599	577
Office	1,376.0	0.124	171.1	14.8	11.6	42.4	62.5	10,701	723
Public Assembly	1,338.0	0.124	166.4	14.2	11.7	43.0	62.5	10,405	733
Public Order and Safety	1,791.0	0.124	222.7	15.5	14.4	52.7	62.5	13,928	899
Religious Worship	440.0	0.124	54.7	10.1	5.4	19.9	62.5	3,422	339
Service	501.0	0.124	62.3	6.5	9.6	35.1	62.5	3,896	599
Warehouse and Storage	764.0	0.124	95.0	16.9	5.6	20.6	62.5	5,942	352
Other	3,600.0	0.124	447.6	21.9	20.4	74.9	62.5	27,997	1,278
Vacant	294.0	0.124	36.6	14.1	2.6	9.5	62.5	2,286	162

Sources

All data in black text King County, DNRP. Contact: Matt Kuharic, matt.kuharic@kingcounty.gov

Energy consumption for residential

buildings

2007 Buildings Energy Data Book: 6.1 Quad Definitions and Comparisons (National Average, 2001)

Table 6.1.4: Average Annual Carbon Dioxide Emissions for Various Functions

http://buildingsdatabook.eren.doe.gov/

Data also at: http://www.eia.doe.gov/emeu/recs/recs2001\_ce/ce1-4c\_housingunits2001.html

Energy consumption for commercial

buildings

EIA, 2003 Commercial Buildings Energy Consumption Survey (National Average, 2003)

Table C3. Consumption and Gross Energy Intensity for Sum of Major Fuels for Non-Mall Buildings, 2003

http://www.eia.doe.gov/emeu/cbecs/cbecs2003/detailed\_tables\_2003/2003set9/2003excel/c3.xls

Note: Data in plum color is found in both of the above sources (buildings energy data book and commercial buildings energy consumption survey).

Carbon Coefficient for Buildings

Floorspace per building

Buildings Energy Data Book (National average, 2005)

Table 3.1.7. 2005 Carbon Dioxide Emission Coefficients for Buildings (MMTCE per Quadrillion Btu)

http://buildingsdatabook.eere.energy.gov/?id=view\_book\_table&TableID=2057 Note: Carbon coefficient in the Energy Data book is in MTCE per Quadrillion Btu.

To convert to MTCO2e per million Btu, this factor was divided by 1000 and multiplied by 44/12.

Residential floorspace per unit

2001 Residential Energy Consumption Survey (National Average, 2001)

Square footage measurements and comparisons http://www.eia.doe.gov/emeu/recs/sqft-measure.html average lief span of buildings, estimated by replacement time method

b		Single Family Homes	Multi-Family Units in Large and Small Buildings	All Residential Buildings
	New Housing Construction, 2001		329,000	1,602,000
	Existing Housing Stock, 2001		26,500,000	100,200,000
	Replacement time:	57.9	80.5	62.5

(national average, 2001)

Note: Single family homes calculation is used for mobile homes as a best estimate life span.

Note: At this time, KC staff could find no reliable data for the average life span of commercial buildings.

Therefore, the average life span of residential buildings is being used until a better approximation can be ascertained.

### Sources:

New Housing Construction,

2001 Quarterly Starts and Completions by Purpose and Design - US and Regions (Excel) http://www.census.gov/const/quarterly\_starts\_completions\_cust.xls See also: http://www.census.gov/const/www/newresconstindex.html

## Existing Housing Stock,

2001 Residential Energy Consumption Survey (RECS) 2001

Tables HC1:Housing Unit Characteristics, Million U.S. Households 2001

Table HC1-4a. Housing Unit Characteristics by Type of Housing Unit, Million U.S. Households, 2001

Million U.S. Households, 2001

http://www.eia.doe.gov/emeu/recs/recs2001/hc\_pdf/housunits/hc1-4a\_housingunits2001.pdf

Transportation Emissions Worksheet

Transportation Emissions Worksheet									
				vehicle related					Life span
				GHG				Life span	transportation
				emissions		MTCO2e/		transportation	related GHG
			# people or	(metric tonnes		year/		related GHG	emissions
		# thousand	employees/	CO2e per		thousand	Average	emissions	(MTCO2e/
Type (Residential) or Principal Activity	# people/ unit or	sq feet/ unit	thousand	person per	MTCO2e/	square	Building	(MTCO2e/ per	thousand sq
(Commercial)	building	or building	square feet	year)	year/ unit	feet	Life Span	unit)	feet)
Single-Family Home	2.8	2.53	1.1	4.9	13.7	5.4	57.9	792	313
Multi-Family Unit in Large Building	1.9	0.85	2.3	4.9	9.5	11.2	80.5	766	904
Multi-Family Unit in Small Building	1.9	1.39	1.4	4.9	9.5	6.8	80.5	766	550
Mobile Home	2.5	1.06	2.3	4.9	12.2	11.5	57.9	709	668
Education	30.0	25.6	1.2	4.9	147.8	5.8	62.5	9247	361
Food Sales	5.1	5.6	0.9	4.9	25.2	4.5	62.5	1579	282
Food Service	10.2	5.6	1.8	4.9	50.2	9.0	62.5	3141	561
Health Care Inpatient	455.5	241.4	1.9	4.9	2246.4	9.3	62.5	140506	582
Health Care Outpatient	19.3	10.4	1.9	4.9	95.0	9.1	62.5	5941	571
Lodging	13.6	35.8	0.4	4.9	67.1	1.9	62.5	4194	117
Retail (Other Than Mall)	7.8	9.7	0.8	4.9	38.3	3.9	62.5	2394	247
Office	28.2	14.8	1.9	4.9	139.0	9.4	62.5	8696	588
Public Assembly	6.9	14.2	0.5	4.9	34.2	2.4	62.5	2137	150
Public Order and Safety	18.8	15.5	1.2	4.9	92.7	6.0	62.5	5796	374
Religious Worship	4.2	10.1	0.4	4.9	20.8	2.1	62.5	1298	129
Service	5.6	6.5	0.9	4.9	27.6	4.3	62.5	1729	266
Warehouse and Storage	9.9	16.9	0.6	4.9	49.0	2.9	62.5	3067	181
Other	18.3	21.9	0.8	4.9	90.0	4.1	62.5	5630	257
Vacant	2.1	14.1	0.2	4.9	10.5	0.7	62.5	657	47

### Sources

All data in black text King County, DNRP. Contact: Matt Kuharic, matt.kuharic@kingcounty.gov

# people/ unit Estimating Household Size for Use in Population Estimates (WA state, 2000 average)

Washington State Office of Financial Management

Kimpel, T. and Lowe, T. Research Brief No. 47. August 2007

http://www.ofm.wa.gov/researchbriefs/brief047.pdf

Note: This analysis combines Multi Unit Structures in both large and small units into one category;

the average is used in this case although there is likely a difference

Residential floorspace per unit 2001 Residential Energy Consumption Survey (National Average, 2001)

Square footage measurements and comparisons http://www.eia.doe.gov/emeu/recs/sqft-measure.html

# employees/thousand square feet Commercial Buildings Energy Consumption Survey commercial energy uses and costs (National Median, 2003)

Table B2 Totals and Medians of Floorspace, Number of Workers, and Hours of Operation for Non-Mall Buildings, 2003

http://www.eia.doe.gov/emeu/cbecs/cbecs2003/detailed\_tables\_2003/2003set1/2003excel/b2.xls

Note: Data for # employees/thousand square feet is presented by CBECS as square feet/employee.

In this analysis employees/thousand square feet is calculated by taking the inverse of the CBECS number and multiplying by 1000.

### vehicle related GHG emissions

Estimate calculated as follows (Washington state, 2006)\_

56,531,930,000 2006 Annual WA State Vehicle Miles Traveled

Data was daily VMT. Annual VMT was 365\*daily VMT.

http://www.wsdot.wa.gov/mapsdata/tdo/annualmileage.htm

6,395,798 2006 WA state population

http://quickfacts.census.gov/qfd/states/53000.html

8839 vehicle miles per person per year

0.0506 gallon gasoline/mile

This is the weighted national average fuel efficiency for all cars and 2 axle, 4 wheel light trucks in 2005. This includes pickup trucks, vans and SUVs. The 0.051 gallons/mile used here is the inverse of the more commonly known term "miles/per gallon" (which is 19.75 for these cars and light trucks).

Transportation Energy Data Book. 26th Edition. 2006. Chapter 4: Light Vehicles and Characteristics. Calculations based on weighted average MPG efficiency of cars and light trucks.

http://cta.ornl.gov/data/tedb26/Edition26\_Chapter04.pdf

Note: This report states that in 2005, 92.3% of all highway VMT were driven by the above described vehicles.

http://cta.ornl.gov/data/tedb26/Spreadsheets/Table3 04.xls

24.3 lbs CO2e/gallon gasoline

The CO2 emissions estimates for gasoline and diesel include the extraction, transport, and refinement of petroleum as well as their combustion.

Life-Cycle CO2 Emissions for Various New Vehicles. RENew Northfield.

Available: http://renewnorthfield.org/wpcontent/uploads/2006/04/CO2%20emissions.pdf

Note: This is a conservative estimate of emissions by fuel consumption because diesel fuel,

2205 with a emissions factor of 26.55 lbs CO2e/gallon was not estimated.

\_\_\_\_\_

4.93 lbs/metric tonne

vehicle related GHG emissions (metric tonnes CO2e per person per year)

average lief span of buildings, estimated by replacement time method

See Energy Emissions Worksheet for Calculations

Commercial floorspace per unit

EIA, 2003 Commercial Buildings Energy Consumption Survey (National Average, 2003)

Table C3. Consumption and Gross Energy Intensity for Sum of Major Fuels for Non-Mall Buildings, 2003

http://www.eia.doe.gov/emeu/cbecs/cbecs2003/detailed\_tables\_2003/2003set9/2003excel/c3.xls